

# 65 Watt Medical Series

Desktop Type



MDM065 - □ X X X

P : C6 / C14 ←      → O / P Voltage  
A : C8 / C18

## Green Mode

Meet CEC , Energy Star Level V , ErP Stage 2  
NO Load Power Consumption Less Than 0.5W

### Features:

- ANSI/AAMI/IEC/EN ES60601-1:2005 (60601 3rd edition)
- IEC 60950 approval
- Means of Protection: 2 X MOPP
- Touch Current : < 100µA
- 100-240VAC Universal Input
- Single Output to 65W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- 2 Years Warranty

Model	O/P Voltage	O/P Current	Watt
ATM065-□120	12V	5.00A	60 W
ATM065-□150	15V	4.34A	65 W
ATM065-□180	18V	3.62A	65 W
ATM065-□190	19V	3.43A	65 W
ATM065-□240	24V	2.71A	65 W
ATM065-□360	36V	1.81A	65 W

## Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.6A-0.7A
Protection	Internal Primary Current Fuse , Inrush Limiting
Configuration	IEC60320/C6, C8, C14, C18

## Output

Load Regulation	±5% ( Typical )
Ripple	1 ~ 2% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	18AWG / 16AWG
Ferrite Core	Yes

## Safety Approvals

CB / UL / cUL / FCC / CE / T-mark(TUV) / PSE  
BSMI: CLASS I / RCM: CLASS II

## Electrical

Topology	Switching Flyback
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100µA
Efficiency	Energy Star Level V , ErP Stage 2 Certified
EMI Conduction & Radiation	Compliance to EN55011 Class B
Harmonic Current	Compliance to EN61000-3-2, 3
EMS Immunity	Compliance to IEC60601-1-2
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

## Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

## Mechanical

Case Dimension	L 119 x W 60 x H 36 (mm) ( Ref. )
Weight	350 g ( Ref. )



RoHS

27